

Perforated Steel Banding ZBM



Type LBV

For fastening:

- Pipe lines on the floor or suspended from ceiling.

Properties:

Material	Steel DK51 D+Z (material no. 1.0226) acc. to DIN EN 10327
Zinc plating	sendzimir zinc plated, 5 - 27 µm
Protective shroud (LBK)	PE

DESCRIPTION

- Steel band with stamped holes for simple installation in zinc plated c

Advantages/Benefits

- Advantageous, simple installation possible.
- Universal fastening possible.
- Flexible length selection.




INSTALLATION

Installation tips

- Simple cutting to size possible with sheet metal shears.
- Floor fastening using the fischer impact nail ED.
- For ceiling suspension in concrete, the fischer nail anchor FNA is recommended.
- Fastening with fischer thread hanger RAH.



TECHNICAL DATA



TECHNICAL DATA

TYPE	TOTAL LENGTH (Mts)	WIDTH B (mm)	THICKNESS (mm)	HOLE DIAMETER D (mm)	HOLES DISTANCE (mm)	TENSILE STRENGTH MAX (Kg)	⁽¹⁾ RECOMMENDED LOAD (Kg)
ZBM 12	10	12	0,7	5	8,5	144	36
ZBM 17	10	17	0,7	7	12	209	52
ZBM 19	10	19	0,7	8	13,5	230	58

⁽¹⁾ SAFETY FACTOR 0,25